


## PRE-CLAD DOOR FRAMES FRONTLINE® COMPOSITE OR TRUCORE® PINE

THE COMPLETE FRAME SOLUTION





PreClad Frames by Frontline® offer a one-step assembly that features a 16 gauge prefinished aluminum exterior integrated with a FrontLine® Composite or TruCore® treated pine base. Use our standard 4-9/16" or 6-9/16" frames, or custom-size your frames using Frontline® extrusions. Add brickmould and crownline nosings and five standard colors – white, black, bronze, sandstone and terratone – and you will have door frames for nearly any application.





## FRAME SPECIFICATIONS

- Base Composite: Woodgrain or primed
   Pine: Finger-jointed clear or primed
- Aluminum 16 gauge
- Paint To AAMA 2603 standard
- Frame Widths Standard: 4-9/16" and 6-9/16"
   Fabricated: 4-9/16" to 12-9/16"
- Mull Posts 2-1/2" and "back-to-back"
- Casing Brickmould, Crownline, Flat Casing

## FRAME DETAILS

- **Sidelite Systems** Continuous head & sill Box units
- Frame Specs Match your wood frame specs
- Frame Preps Sill angle, head dado, mull headers, mull haunch, hinaes & deadbolts
- **Weather-Seal** Installed, loose or none Q-lon 650 or 730

Beige, black, bronze or white

Variable Depths - FLTA-77 for ripped frames
 FLTA-60 - 2" Frame Extender

## FRAME FEATURES

- Assembles the same as a wood frame:
   Cuts clad unit assemble time in half
- Custom Frame Depth:
  Fabricate the jamb depth you need
- Composite Base:
   Rot, decay, mold, insect and split proof
   Woodgrain stains like a fiberglass door or paint Prime paint
- TruCore Pine Base:
   Rot, decay, mold, insects and split resistant clear or primed treated for life
- Storm Door Compatible
- 16 Gauge Aluminum Exterior
   Heavy-duty and dent resistant
- Limited Lifetime Warranty
  See FrontLine® website for complete information
- Transom Compatible:
   Complete selection available see website



www.frontlinebldg.com | sales@frontlinebldg.com | 920-393-1340